

# J2 Universal UPS

## Uninterruptible Power Supply



### Key Features

- > Smart Low Voltage DC UPS
- > Long runtimes 1.5-5 hours, depending on POS system and configuration
- > Lithium-ion Battery Technology
- > Orderly system shut down on low battery
- > Protects POS data from power interruptions
- > Protects against low line voltage
- > Eliminates the need for AC line conditioning
- > Installs in base of J2 6XX series POS
- > UPS status reported by smart interface
- > Status LED for UPS status
- > Smart UPS interactive software
- > Compatible Windows XP, 7, 8, Server and Linux
- > Compatible with most all J2 POS Systems

### Benefits

- > Computer data protected against power loss
- > Full AC power line protection
- > POS can still operate with power outage
- > Very small foot print, mounts inside POS
- > Very energy efficient
- > Low cost of ownership



## J2 Universal UPS Uninterruptible Power Supply

### Small - Power efficient - Very long run times

Retailers using touchscreen POS systems from J2 can now enjoy a breakthrough in UPS support that gives protection way beyond that currently available. Whilst an external AC UPS can provide run times of 5-30 minutes, the J2 Universal UPS can support run time from 1.5-5 hours of run time depending on the J2 systems used and configuration.

One big advantage of using the J2 UPS is that all peripheral power by the J2 POS will still be powered when running on the UPS. When using the J2 680/680L this includes the printer.

This enables retailers to continue trading as normal, including doing cash transactions and printing, with no corruption or loss of data. Before it runs out of power, the system will trigger a safe and timely shut-down. The UPS unit is competitively priced, making it an affordable and wise investment.

The J2 universal UPS will work with most all of J2 POS computer products. This includes the J2 225/480/615/625/630/680 and 680L. For the J2 6XX series the UPS mount in the base of the unit where the power supply is normal

mounted. When using the UPS option the power supply will be mounted external to the unit. For the J2 225 and the J2 480 the UPS will be mounted outside the unit.

Available in both 2600mAh and 5,200mAh versions depending on run time requirements.

**All J2 products  
are RoHS and  
WEEE compliant**

# J2 Universal UPS

## Uninterruptible Power Supply



### Electronics

Microcontroller based  
 Smart charger controller  
 Dual Li-ion battery packs with safety circuits  
 Safety battery disable switch for shipment and storage

### I/O Ports

+19VDC power input from POS power supply  
 +19-14VDC power output to POS system  
 Serial port connection to-from POS system  
 UPS Status LED

### Average Run Times

J2 225	5 hours
J2 625	4 hours
J2 615	3 hours
J2 630	3 hours
J2 480	3 hours
J2 680L	2.5 hours
J2 680	2 hours

\*Note: J2 225/615/625/630 can run using one battery pack, run times are 45% of dual pack

### OS Support

Generic UPS driver supported for XP and Linux  
 J2 Smart UPS driver for Windows XP, POSReady 2009,  
 POSReady 7, Windows 7, Windows 8

### Environmental


Temperature	Operational	0°C ~ 40°C
	Storage	-20°C ~ 55°C
Safety	LVD external adapter ULc/us ,CE, TVU, others	

### Options

Dual or Single Battery pack, 2,600mAh or 5,600mAh

### Dimensions


Width 152mm  
 Depth 80mm  
 Height 46mm



Smart UPS Driver



Electronics



Block Diagram UPS – Power Supply AC Isolation Path

### Contact

Headquarters	USA Office	Australian Office
J2 Retail Systems Ltd. J2 House Clayton Road, Birchwood Warrington WA3 6RP United Kingdom	J2 Retail Systems Inc. 9251 Irvine Boulevard Irvine CA 92618 USA	J2 Retail Systems Pty Ltd Unit 6 83/85 Boundary Road Mortdale NSW 2223 Australia
T 44 (0) 1925 817003 F 44 (0) 1925 811989	T (714) 669-3111 F (714) 669-3133	T 02 9584 5222 F 02 9584 1500