

# J2 580

## Integrated Touchscreen Computer



### Key Features

- > 15" TFT LCD
- > Resistive touchscreen
- > Thick or thin client technology
- > Hard disk drive
- > Compact flash
- > 3 track MSR option
- > ibutton option
- > Fingerprint reader option
- > 4 external serial ports
- > 5 external USB ports
- > Secondary display port
- > OPOS drivers

### Benefits

- > Low cost of ownership
- > Fan or Fanless
- > Range of processors to suit all applications
- > Base, pole or wall mountable using standard VESA mount
- > Designed by J2 Retail Systems' research & development team



## J2 580 Integrated Touchscreen Computer

The J2 580 takes all of the previous J2 developments to the next level. A feature rich, powerful device with a vast array of processing options, the J2 580 will become the hardware of choice for the retailer who demands the best.

The J2 580 is unique in design. Building on the J2 values and innovative design practices of the past J2 have produced a product that will not only meet the requirements of retailers today, but future proof their investment for many years to come.

There are 3 main variants of this model available. Utilising the latest technology from Intel the 580 has an entry level specification adopting a fanless approach progressing to the high specification Intel processors that accommodate power hungry applications.

Accessibility is the key to machine maintenance or upgradeability. The motherboard can be easily removed and exchanged, upgrades to the memory modules can be easily undertaken as the tray housing the technology slides in and out with the greatest of ease. A complete motherboard upgrade can be carried out in less than 10 seconds! The HDD is easily accessible as it too is housed on a removable tray.

The footprint of the J2 580 is particularly compact making it ideal for the space conscious retailer.

The 580 thick or thin configurations support the standard Microsoft operating systems XP, WePOS, CE.NET and XPe, further demonstrating its versatility. The 580 is equally proficient with the many flavours of Linux.

**All J2 products  
are RoHS and  
WEEE compliant**

# J2 580

## Integrated Touchscreen Computer



### System Board

CPU	INTEL 1 GHz Celeron M, Fan-less INTEL 1.5 GHz Celeron M 1MB Cache, 400MHz FSB INTEL 1.8 GHz Pentium M 2MB Cache, 533MHz FSB
Chipset	Intel
Graphic Controller	Integrated, Intel
Memory	2 Slots, SO-DIMM, up to 2GB

### LCD & Touchscreen

LCD	15" TFT 1024x768, chipset scaling for 800x600
Touch Screen	5 Wire Resistive, 35M touches (580RT)
Brightness	250 cd/m2

### I/O Port

#### External I/O

Serial	4 RD-232, 2 with +5/12Vsupport, 1 with RD422/RS485 option
USB	5 USB 2.0. 4 in cable well one on side of unit
Parallel	1 ECP/ EPP
Cash Drawer	RJ11, 12V or 24V
PS/2	Supported with optional USB-PS/2 adaptor
LAN	10/ 100
Audio	Microphone/Line in jack, Headset/Line out jack
Power	19VDC 4.75A, 100~240V~1.4A 50/60Hz adapter in base, locking connector

#### Internal I/O

USB	2
Serial	For internal resistive touch controller
Speakers	2 x 2 watt stereo speakers

### Storage

HDD or CF	Quick change, slide in 2.5" Serial ATA (SATA) HDD or Compact Flash Adapter
-----------	---

### Expansion

Mini-PCI	One internal Mini PCI slot
----------	----------------------------

### Environment

EMI	CE/FCC Class A
Safety	LVD, External adapter UL c/us, CE, TUV, others
Operating Temperature	0~40°C
Dust & Water Proof	

### Options

MSR	3 track ISO, OPOS support
Customer Display	Rear Display, 20 Character x 2 Line VFD, 9mm character height, OPOS support
Secondary Display	12" LCD 800x600, standard Windows extended desktop, Power from 580 (optional)
Biometrics	Digital Persona Finger Print reader, J2 MSR/iButton ID emulation software
Dallas Key	Dallas Key iButton reader
Wireless LAN	802.11b/g/n, internal
UPS	Integrated Intelligent Uninterruptible Power Supply, 2 hour back up

### Software Support

O/S Support	XP, WEPOS (CF or HDD), XP embedded (CF or HDD), Linux, DSL Linux (CF), Windows CE 5.0 (Jan 2008)
OPOS	OPOS driver for MSR, Customer Display, Cash drawers, Finger Printer Reader

### Dimensions

Width	365mm
Depth	220mm
Height	310mm



Connectivity



VESA Capable



Removable Mainboard



HDD

### Contact

#### International Headquarters

J2 House  
Clayton Road,  
Birchwood  
Warrington,  
WA3 6RP  
United Kingdom

T 44 (0) 1925 817003

F 44 (0) 1925 811989

W [www.j2retailsystems.com](http://www.j2retailsystems.com)

#### US Office

2691 Dow Avenue,  
Building A  
Tustin  
CA 92780  
USA

T 1 714 669 3111

F 1 714 669 3133

W [www.j2retailsystemsusa.com](http://www.j2retailsystemsusa.com)

